





TQLZ VIBRO PRE CLEANER

TQLZ VIBRO PRE CLEANER

TQLZ Vibro Pre Cleaner is widely used for cleanning miscellaneous from paddy, maize, and wheat. etc grains. It has many advantages such as: lower power comsumption, light structure but stable, good appearance, and good performance.

appearance, and good performance.		
MODEL	CAPACITY (T/H)	POWER (KW)
TQLZ80	5-8	2×0.2
TQLZ100	8-12	2×0.37
TQLZ125	12-15	2×0.37
TQLZ150	15-18	2×0.55
TQLZ180	18-22	2×0.55



TQLM ROTARY SIEVE





TQLM Rotary Sieve is separating paddy from miscellaneous raw materials. It also has inlet and outlet suction feature, which makes the working environment less dust and clean.

MODEL	CAPACITY (T/H)	POWER (KW)
TQLM80	20/6.4	0.75
TQLM100	25/8	0.75
TQLM125	32/10	0.75
TQLM150	38/12	0.75

TZQY COMBINED CLEANER

TZQY Series of combined cleaner, including function of drum cleaning and destoning, are an idea equipment for cleaning all kinds of impurities and stones in the raw material.

MODEL	CAPACITY (T/H)	POWER (KW)
TZQY 75/65	3.2-4.8	2.2
TZQY 100/86	6.5-7.5	2.2



TQSX GRAVITY TYPE DESTONER



TQSX Gravity Type is using for removing heavy impurities from paddy, wheat, white rice. The design of the machine is based on simple, stable, durable ideal, which gives the machine the feature of easy maintain and stable.

MODEL	CAPACITY (T/H)	POWER (KW)
TQSX 56	1.5-2T	0.55KW
TQSX 85	2.5-3T	0.75KW
TQSX 100	4-4.5T	0.75KW
TQSX 125	5.5-6T	1.1KW
TQSX 168	7.5-9T	1.5KW


TQSX SERIES SUCTION TYPE DESTONER

TQSX Suction Type Destoner can be used in rice milling and grains for destoning, drivend by air-pressure makes the stones and raw material moving to opposite direction. It has exceleent performance for separating paddy and stone. There is a light equiped in the chamber of the machine makes the inside working of the machine can be seen and the air volume can be controled, air meter is also equiped.

MODEL	CAPACITY (T/H)	POWER (KW)
TQSX120x2	7-10	0.3x2
TOSX150x2	10-12	0.37x2



TOSF DESTONER



By using double deck structure, the TQSF machine can get rid of stone from the grain effectively. The second sieve can remove the stone for the grains that has been processed by first sieve so the performance of the destoner is better.

MODEL	CAPACITY (T/H)	POWER (KW)
TQSF(TQSS)120	7-10	0.3×2+0.75
TQSF(TQSS)150	11-15	0.3×2+0.75

MLGT (MLGQ) HUSKER

EQUIPMENT SERIES

MGCZ PADDY SEPARATOR -

MLGT (MLGQ) HUSKER


MLGT Series Husker is the most common husker.It is excellent designed with low maintenance and high output. It is suitable for most rice mill. The MLGQ series husker has same output as mlgt series but it is penumatic type with automatic operation.

MODEL	CAPACITY (T/H)	POWER (KW)
MLGT25B(MLGQ25B)	2.5-3.6	5.5
MLGT36B(MLGQ36B)	4-4.8	7.5
MLGT51B(MLGQ51B)	6-6.8	n




MGCZ PADDY SEPARATOR

MGCZ Paddy Separator can separate paddy and rice. It has several sieves that can separate the mixture of raw materials effectively. The more sieves it has, the biger capacity it has. The are two type of the machine, one is single eccentic and the other is double eccentric.



DOUBLE BODY PADDY SEPARATOR



MGCZ Double Body Separator is newly designed with balance and stable idea. The output of the machine is big and it is very easy to maintain by using high quality stainless spare parts. It is also easy to operate by automatic design.it is ideal for large rice mill plant.

MODEL	CAPACITY (T/H)	POWER (KW)
MGCZ46×20×2	5-6T	3KW
MGCZ60×20×2	6-8T	4KW

MGCZ SINGLE BODY SERIES


MGCZ series of paddy separator are traditional machine for small capacity rice mill plant. It separates brown rice from the grain mixture by taking advantage of the difference of the gravity and surface frictional modules between paddy and brown rice. It is very popular machine over the world because it can improve the whole rice output greatly and improve economic benefit enormously.

MODEL	CAPACITY (T/H)	POWER (KW)
40x20	2.5-3T	1.5KW
46x20	2.2-2.8T	1.5KW
50x20	2.5-3T	1.5KW
60x20	3-3.8T	1.5KW
70x20	4-5T	1.5KW

grain by and e. It is prove enefit

MGCZ SINGLE BODY SERIES

TS25B/TS25-1 EMERY ROLLER RICE WHITENER




TS25B Rice Whitner can Polish Brown Rice into White Rice. The machine designed idealy for parboiled rice and with low maintenance.

MODEL	CAPACITY (T/H)	POWER (KW)
TS25B/TS25-1	2-2.5	22-4P+3


SM18E EMERY ROLLER RICE WHITNER

SM18E RICE WHITNER is modified for processing parboilied price, by equiped with emery roller and rubber kicking roller, the rice can be polished beautifull.

MODEL	CAPACITY (T/H)	POWER (KW)
SM18E	2-2.5	22-4P+3



NF15A RICE WHITNER



NF15A Whitner is suitable for small to medium rice plant, it is easy to maintain and the cost of maintenance is low. It has air jet desigh which can lower the temperature of the rice. By using the adjustable weight, the grade of the finishing rice can be adjusted.

MODEL	CAPACITY (T/H)	POWER (KW)
NF15A	1-1.5T	11-18.5
NF15B	1-1.5T	11-18.5
MNMF15B	1-1.5T	15-22

MNSL DOUBLE-ROLL WHITENER

MNSL double-roll rice whitener is a newly designed power-saving vertical rice whitener. It can reduce elevator with two roll processing. Both emery roller and iron roller can be equipped, big yields with strong air aspiration and low rice temperature.

MODEL	CAPACITY (T/H)	POWER (KW)	
MNSL21.5/16	1.7-2	37	
MNSL21.5/21.5	2.5-3.3	30-37	







MNML Series Emery Rolle Whitner is almost same as SATAKE VTA Model and suitable for large scale rice mill. By using vertical structure, it has good performance of low rice temperature, high output and lower rice broken rate. It is easy to maintain by equipting with high quality spare parts.

MODEL	CAPACITY (T/H)	POWER (KW)	
MNML30(VTA5)	3-4T	30-37	
MNML40(VTA7)	4-5T	37-45 45-55	
MNML46(VTA10)	5-7T		
MNML51	8-10T	55	

MNSL VERTICAL TYPE

MNSL double-roll rice whitener. This is a newly designed power-saving vertical rice whitener. It can reduce elevator with two roll processing. Both emery roller and iron roller can be equipped, big yields with strong air aspiration and low rice temperature.

MODEL	CAPACITY (T/H)	POWER (KW)	
MNSL 25	2.5-3T	22	
MNSL 30	4-5T	45	



KB40, 60 SILKY WATER POLISHER



KB40 60 Silky Water Polisher is excellent design for polishing rice. By using of this silky water polisher, rice value can be added significantly. Once rice been polished by the machine, the rice is no need to wash before cooking


MODEL	CAPACITY (T/H)	POWER (KW)	
KB40(MPGT40 CMG16)	2.5-3.5	37KW	
KB60	4-6	45KW	

EQUIPMENT SERIES

MPGT SILKY WATER POLISHER

MPGT Series Silky Water Polisher is well known product in the market. It has lower broken rate and excellent performance, which can make the storage time longer for the rice and add value to the rice.

MODEL	CAPACITY (T/H)	POWER (KW)	
MPGT14.5	1-2	30	
MPGT16	2-2.5	37	
MPGT16×2	2-2.5	45	
MPGT19	2.5-3	45	
MPGT19×2	3-6	55-75	
MPGT21	3.5	45	
MPGT21×2	3.5-4	55	
MPGT40(KB40 CMG16)	2.5-3.5	37-45	
MPGT50	4-5	45	







MPGL double-roll water polisher is flexible for combination of two rollers to be in series or parallel. Unique design of polishing chamber make the rice can be polished evenly. The performance of polished rice can be more shinning and smooth.

MODEL	CAPACITY (T/H)	POWER (KW)	
MPGL16	2-2.5	37	

MMJP (MMJX) RICE GRADER

MMJP & MMJX White Rice Grader is widely used for grading rice. It can separate rice into four or five grade, which can help to add more value to the higher grader rice.

MODEL	CAPACITY (T/H)	POWER (KW)	
MMJP(MMJX)80×4	1.8-2.2	1.1	
MMJP(MMJX)100×4	2.5-3	1.1	
MMJP(MMJX)100×5	2.8-3.2	1.1	
MMJP(MMJX)112×4	3.5-4	1.1	
MMJP(MMJX)112×5	3.8-4.2	1.1	
MMJP(MMJX)125×5	5-5.5	1.1	
MMJP(MMJX)150×5	5.5-6.5	1.5	





QUALITY KA RAJA BULLET RAJA

Mini Rice Mill Machine is used to automate the process of hulling paddy into rice while separating full rice, broken rice and bran.

Where full rice is used for mass consumption. The husk and broken rice can be sold at farms to feed livestock.

The biggest advantage of this machine is that its easy to operate and due to its small size it doesn't require much space for installation. You just have to put on the power so that the process of hulling rice can be easily realised. This machine is widely used in agriculture, farms etc.

SALIENT FEATURES:

- Hourly production is 120kgs to 150kgs, full rice rate is 80-85%
- Low Maintence Cost.
- Low Elecricity Consumption.
- Easy and fast installation with no foundation required at the time of installation.
- Easy to operate just plug and use.

MAIN PERFORMANCE PARAMETERS

Item	Power	Output	Voltage	Frequency	Sound	Size (length x width x height)
6N-40	2.2 kW	> 120kg/h	220V	50Hz	<93dB(A)	78 x 38 x 106 (cm)



- Complete Rice Mill Plant solution can be supplied.
- Unique design for each case to meet customer requirements.
- Best cost effective ration
- Professional services






RICE MILL PLANT 100T PER DAY

RICE MILL PLANT 150T PER DAY

Emery roller, screen, rubber roller, polishing roller, Iron roller, Silky water polisher roller, warmer roller etc... spare parts can be supplied for all chinese and satake and buhler rice machines.



LTJM2099 RICE TESTING MACHINE



SCREENS



EMERY ROLLER



IRON ROLLER



KICKING ROLLER



POLISHER ROLLER



RUBBER ROLLER



RUBBER SPRING



SCREW ROLLER



INNOVA AGRITECH PRIVATE LIMITED 308, G.T. Road (N), Salkia, Howrah - 711 106, W.B., India

Ph: +91 33 2655 9421, +91 7003316495 email: innovaagritech@gmail.com